



USER MANUAL FOR ACON AIRTRACKS

These instructions apply to the following ACON airtrack models: airtrack 3m/10ft, airbeam 3m/10ft, airblock 100x60cm/40x24in, airspot Ø100cm/Ø40in, airroll 90x120cm/24x47in, airroll 60x120cm/35x47in

AIRTRACK 3m/10ft 	AIRBEAM 3m/10ft 	AIRBLOCK 100x60cm/40x24in 
AIRSPOT Ø100cm/Ø40in 	AIRROLL 90x120cm/24x47in 	AIRROLL 60x120cm/35x47in 

Thank you for purchasing one of our safe and fun products! With this manual we want to describe how to use Acon airtracks. Please make sure to read through the instructions carefully before using your airtrack. Should anything be unclear, do not hesitate to contact our customer support! We hope you enjoy your new equipment.

GENERAL INSTRUCTIONS

Always store and transport the airtrack in its carrying bag. Do not use the airtrack if it is damaged or leaking air.

Choose an appropriate area to set up the airtrack. Ensure that there is nothing sharp underneath the airtrack (such as rocks, gravel, etc.) when setting it up to avoid damaging the airtrack. If you use the airtrack outside, set it on level and soft ground, preferably on top of a protective tarp or fabric.

To clean the airtrack surface, wipe it with lukewarm soapy water. Avoid strong cleaning solutions. Before rolling up the airtrack for storage, ensure that the airtrack is clean and dry.

The recommended temperature for airtrack use is -10–+30°C/14°F–86°F and for storage it is at least +5°C/41°F (not recommended to be stored in direct sunlight). Airtracks can bear 200 kg/m² / 440lb/10.76 ft².

REACH



HAND PUMP USER INSTRUCTIONS

Inflating the airtrack: Remove the airtrack from the carrying case and roll out fully so that the valves are visible. Depending on the model, the airtrack can have one or two valves; if there are two valves, you can use either to inflate or deflate the airtrack. Only use the pump that is included with the airtrack.



Open valve cover (1). Ensure that the valve button is in the up-position (2). Place the head of the pump tube into the valve and twist to the right so that the pump and valve connect tightly (3).

Recommended pressure for airtrack is 5-6 PSI. The bounciness of the airtracks depends on how much pressure you put in it. Our recommended pressure level is 5-6 PSI but the most optimal pressure depends on the users' preferences. Pump until the desired air pressure level is seen on the pump's air pressure meter. Remove the head of the pump tube by twisting to the left. Put the valve cover back in place. Ensure that the valve cover is properly in place to avoid air leaking from the airtrack.



Deflating the airtrack: Push the valve button into the down-position and the valve will open (2).

If air leaks around the valve, follow these steps:

1. Remove the valve key from its packing case.
2. Open the valve cover and place the valve key in the valve.
3. Turn the valve key clockwise until there is no space between the valve and the airtrack. **Do not turn the key counterclockwise** as this will cause the valve to loosen, leak air, and eventually detach from the airtrack.
4. Close the vent and check to see if the leak stopped.





CONTACT US

EUROPE

Email: customercare.eu@acon24.com
Tel: acon24.com/pages/customer-service
acon24.com

USA

Email: customercare.us@acon24.com
Tel: +1-866-297-5234
us.acon24.com

MANUALS

acon-manuals.com

